

8851 U001



GREAT FEATURES

9 Minimum transport width

All **Pro** series rotary rakes are equipped with rake arms that are easily removeable and that are stored towards the front of the rake when in transport position. The protection guards lift into vertical position.



OPTIONAL

10 Hydraulic shock absorber

A hydraulic shock absorber can be mounted on the 3 point hitch models to increase stability on uneven terrain.



STANDARD EQUIPIM.

11 Tandem axle

Standard equipment for all models. Increases the ability to follow of contours in the roughest conditions while maintaining stability and raking performance.

TECHNICAL CHARACTERISTICS	3PT HITCH			PULL TYPE			
		350	385	450	350	385	450
Working width	mt/ft	3,5/11' 6"	3,85/12' 8"	4,5/14' 9"	3,5/11' 6"	3,85/12' 8"	4,5/14' 9"
Average windrow width	mt/ft	0,9-1,2/3' 4"	0,9-1,2/3' 4"	0,9-1,2/3' 4"	0,9-1,2/3' 4"	0,9-1,2/3' 4"	0,9-1,2/3' 4"
Transport width	mt/ft	1,75/5' 9"	1,75/5' 9"	1,75/5' 9"	1,75/5' 9"	1,75/5' 9"	1,75/5' 9"
Attachment/cat.		2° cat	2° cat	2° cat	STANDARD 1°CAT PREDISPOSED 2/3°CAT	STANDARD 1°CAT PREDISPOSED 2/3°CAT	STANDARD 1°CAT PREDISPOSED 2/3°CAT
Arms for rotor	nr	9	11	11	9	11	11
Tine arms per rotor	nr	27	44	44	27	44	44
Tine diameter	mm	9,5	9,5	9,5	9,5	9,5	9,5
Tires		15.600-6	16.650-8	16.650-8	15.600-6	16.650-8	16.650-8
Tandem axle		STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
Pto	rpm	540	540	540	540	540	540
Required Pto hp/Kw	kW/hp	15/20	19/26	22/30	15/20	19/26	22/30
Appropriate working speed	kmh/mph	15/9,3	15/9,3	15/9,3	15/9,3	15/9,3	15/9,3
Weight	kg/lbs	390/860	460/1014	600/1322	430/948	490/1080	640/1411
Hydraulic lift standard for a quick and easy transport	-	-	-	-	-	STANDARD	STANDARD
Distance from the ground max	mm/inch	-	-	-	190/7,5"	390/1' 4"	390/1' 4"

OPTIONAL EQUIPMENT

Additional support wheel	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST	ON REQUEST
Hydraulic shock absorber	ON REQUEST	ON REQUEST	ON REQUEST	-	-	-

MORE SUCCESS WITH TONUTTI PRODUCTS



Mower conditioner RMC7 Tedders GTH PRO 660 Finger wheel rake DOMINATOR V14 WOLAGRI - Variable Chamber Round baler SYRIA 160



TONUTTI reserves the right to make changes or add improvements at any time without notice. The information contained here in is general in nature and is not intended for specific application purposes.

tonutti
SINCE 1864
Always one step ahead®

Tonutti Italy
Via Gino Tonutti 3 - 33047
Remanzacco (UD) Italy
Tel. + 39 0432 667015
Fax + 39 0432 668282
info@tonuttigroup.com
www.tonuttigroup.com

Tonutti U.S.A.
1909 Thomas Road
Memphis, TN 38134
Phone (901) 385 8841
Fax (901) 385 8288
info@tonuttiusa.com
www.tonuttigroup.com

Tonutti Russia
T. W. Limited
3 Tekhnicheskaya Street
Perm, 614070 Russia
Phone 007 (3422) 909096
Fax 007 (3422) 909096
twltd@perm.ru
www.tonuttigroup.com



Since 1864, we have put our customers and their needs at the heart of our business, always ready to listen and better understand their requests.

Thanks to the satisfaction and loyalty of our customers, the dedication and expertise of our employees, and our commitment to innovation, we continue to be a market leader by bringing the lessons we learn throughout the world to our customers in the form of improved products and farming concepts.

We are committed to:

- our customers
- continued growth
- worldwide leadership through the development of superior products
- the environment through the design and manufacture of eco-friendly products with reduced fuel consumption requirements

Today, the Tonutti Group employs more than 500 people across three continents with sales and manufacturing facilities in the United States, Italy, France, Russia, and China providing us global coverage with local knowledge.

At Tonutti Group, we have been providing farmers with innovative solutions for over 145 years. Our commitment to innovation and growth ensures that we will continue to be a leader for generations to come.



The old "farie" - 1864

The new Tonutti's GR **Pro** Line offers five cost-effective sizes from 11'6" to 14'9" and each size is available in 3pt hitch or trailed models.

The GR **Pro** Series combines high performance with heavy duty construction and is designed to last longer in more difficult working conditions.

These capabilities combined with our spiral cam designed gearbox and redesigned height adjustment system gently form windrows for maximum yield.



1 Tines adjustment
The tines follow the terrain contours without disturbing the soil. Height adjustment is made directly from the tractor seat.



2 High ground clearance - trailed models
High ground clearance allows easier passing over formed windrows.



3 Hydraulic lift is standard equipment on trailed models GR Pro 385 and 450.
This can be actuated from the tractor seat for quick and easy transport.



8 Additional front wheel
The optional front wheel can be mounted to the front of the machine to further improve ground contour and reduce debris in the windrow.



7 Pivoting 3 point hitch
This feature makes working on uneven terrain or on slopes easy and efficient. The rake moves independently from the tractor in order to follow the contours of the terrain.



6 Windrow curtain with telescopic adjustment
The windrow curtain is easily adjustable without tools. Just remove the pin to place in working or transport position. A spring aids in lifting the curtain into vertical position.



5 Rake arms specially shaped with 3 bends
These specially shaped rake arms allow for a better windrow forming and are easily and quickly removeable. The three spiral tines are designed for durability yet are gentle or forage to prevent damage during raking.



4 Tough, reliable, no-maintenance gearbox
To insure durability our internal oil bath lubrication system is fully protected from dirt and dust.

Pro LINE

**SIMPLE.
EFFICIENT.
RUGGED.**